



Belt Conveyor



Zenith conveyor is adaptable for stationary and mobile crushing plants, it is widely used in mining, metallurgical and coal industry to transfer sandy or lump material, or packaged material. The transfer system can be one single or multi-conveyers or combined with other transfer equipments according to various transferring requirements. And Zenith belt conveyor can be installed horizontally or aslope to meet the needs of different transfer lines.

Belt Conveyor Features:

- 1) High capacity
- 2) Standard parts
- 3) Simple structure
- 4) Easy Maintenance

Belt Conveyor Technical Data:

Width(mm)	Length(m)/Power(kw)			Speed(m/s)	Capacity(t/h)
	≤12	12~20	20~25		
400	2.2	2.2~4	3.5~7.5	1.25~2.0	30~60
	3	4~5.5	5.5~7.5		
500	≤12	12~20	20~30	1.25~2.0	40~80
	4	5.5	7.5~11		
650	≤6	6~15	15~30	1.25~2.0	80~120
	4	5.5	5.5~15		
800	≤10	10~20	20~40	1.25~2.0	200~320
	5.5	7.5~11	11~12		
1000	≤10	10~20	20~40	1.25~2.0	290~480
	7.5	11	15~30		

If there is change of the above specification, it subjects to the newest products' specifications.

Contact E-mail webmaster@zenithdream.com